

PORTABLE ELECTRIC SALAMANDER



HEAT WAVE™ FES-SERIES



- Safety yellow heater enclosure with safety screens on both air intake and output openings.
- Optional 25' long SO type cord, ready for plug attachment is available for each model.
- Long-life finned tubular heating elements
- Thermostat adjustment 40° to 100° F
- Magnetic contactor
- Automatic reset
- High-limit thermal cutout switch
- Fan only switch
- 10" wheels
- 800 CFM-15KW units - 1100 CFM-30KW units



MODEL	UPC # 686334	KW	BTU's	VOLTS	PH	AMPS	TEMP RISE	WT.
FES-1520-3A	886017	15	51195	208	3	42	45°F	65 lbs.
FES-1524-1A	886079	15	51195	240	1	63	45°F	69 lbs.
FES-1524-3E	886024	15	51195	240	3	36	45°F	65 lbs.
FES-1548-3E	886031	15	51195	480	3	18	45°F	65 lbs.
FES-3048-3A	886055	30	102390	480	3	36	90°F	83 lbs.
FES-3060-3A	886062	30	102390	600	3	30	90°F	83 lbs.

OPTIONAL 25' POWER CORD		
Model #	UPC #	TYPE
3164001	316408	6/4 SO
8805300	880534	4/3 SO
3164001	316408	6/4 SO
3164201	316422	12/4 SO
3164001	316408	6/4 SO
8805100	880510	8/4 SO

10KW - 240V - 1 PHASE FACTORY PRE-WIRED MODEL WITH 10 ft. CABLE & STRAIGHT BLADE RANGE PLUG FOR USE WITH A STANDARD RANGE OUTLET.

MODEL	UPC# 686334	KW	BTU's	VOLTS	PHASE	AMPS	TEMP RISE	WT.
FES-1024-1CA	200134	10	34130	240	1	42	30°F	60 lbs.

AVERAGE MINUTES TO ACHIEVE TEMPERATURE RISE*						
BUILDING SIZE:	1000 SQ. FEET		1500 SQ. FEET		2000 SQ. FEET	
HEATER:	TEMP RISE		TEMP RISE		TEMP RISE	
	20°F	40°F	20°F	40°F	20°F	40°F
	70 min	140 min	105 min	210 min	---	---
	47 min	94 min	71 min	142 min	94 min	188 min
30 KW	23 min	46 min	35 min	70 min	47 min	94 min
* Based on a 15' ceiling height - lower ceiling height will reduce time required						



MODEL #:
FES-1024-1CA

WALL MOUNTING KIT FOR ELECTRIC SALAMANDER



MODEL #:
WMK-FES

- WALL / CEILING MOUNT KIT FOR EXISTING MODEL
- KIT INCLUDES YOKE AND MOUNTING BRACKET TO CONVERT AN EXISTING FES PORTABLE MODEL TO A "YES" (Yoke-Mounted Electric Salamander) SUSPENDED UNIT

MODEL	UPC # 686334	DESCRIPTION	FITS MODELS	WT.
WMK-FES	480413	Wall Mounting Bracket Kit	All FES Models	60 lbs.

