

PORTABLE INFRARED HEATERS



**2.0KW & 4.5KW
STAND**

**6.0KW & 13.5KW
HAND CART**

FOR INDOOR OR OUTDOOR USE

- Factory installed U-shaped metal sheath infrared heating elements have an average 5000 hour life
- Heavy duty protective wire screens
- GOLD anodized aluminum internal reflector
- Double side wall housings to reduce operating temperatures
- 6.0 and 13.5KW heaters have double top baffles to reduce operating temperatures.
- 60° symmetrical heat pattern
- Optional 25' long SO type cord, ready for plug attachment is available for each model.

SQUARE FOOTAGE HEATED	NON-PROTECTED AREA		SEMI-PROTECTED AREA	
	BELOW	ABOVE	BELOW	ABOVE
	35 °F	35 °F	35 °F	35 °F
1.8KW / 2.0KW	25	36	40	50
4.5 KW	64	75	90	125
6.0KW	85	100	120	150
13.5KW	192	225	270	375

UPC 686334	MODEL	KW	BTU's	VOLTS	PH	AMPS	WT.
881739	FHK-224-1A	2.0	6,826	240	1	8.3	17 lbs.
881753	FHK-248-1A			480	1	4.2	
881784	FHK-424-1A	4.5	15,359	240	1	18.8	24 lbs.
881807	FHK-448-1A			480	1	9.4	
882910	FHK-624-3A	6.0	20,478	240	3	14.4	37 lbs.
					1	25.0	
882934	FHK-648-3A			480	3	7.5	
					1	13	
882965	FHK-1324-3A	13.5	46,076	240	3	33.0	65 lbs.
882989	FHK-1348-3A			480	3	17.0	
					1	29.0	

OPTIONAL 25' POWER CORD		
UPC 686334	MODEL	TYPE
880435	8804300	16/3 SO
880435	8804300	16/3 SO
880459	8804500	12/3 SO
880466	8804600	14/3 SO
880497	8804900	14/4 SO
880442	8804400	10/3 SO
880497	8804900	14/4 SO
880466	8804600	14/3 SO
880510	8805100	8/4 SO
316422	3164201	12/4 SO
880527	8805200	8/3 SO

SPECIAL BUILD MODELS:

units operating at 208V, 277V or 600V

FACTORY PRE-WIRED MODELS WITH 15 ft. CORD & GROUNDED PLUG



UPC 686334	MODEL	TYPE	KW	BTU's	VOLTS	PHASE	AMPS	WT.
881715	FHK-212-1CA	STAND	1.8	6,143	120	1	15.0	18 lbs.
882798	FHK-624-1CA	CART	6.0	20,478	240	1	25.0	40 lbs.