
## LPD - LOW PROFILE DIRECT DRIVE CENTRIFUGAL ROOF/SIDEWALL EXHAUSTER





Breidert Air Products, Div. of Soler & Palau Ventilation Group certifies that the Models LPD shown herein are licensed to bear the AMCA Seal. The ratings shown are based on test and procedures performed in accordance with AMCA Publication 211 and AMCA Publication 311 and comply with the requirement of the AMCA Certified Ratings Program.



SIZE		AVERAGE SHIP WT. LBS.					
	Α	В	С	D	E	F	G
6	16 1/2	7	16 1/2	11	14 3/4	113/4	12
8	16 1/2	7	16 1/2		14 3/4	3/4	15

A - Outside diameter of unit.

B - Height of unit above top of curb.

C - Inside dimension of square curb cap.

D - O.D. backdraft damper (box frame type).

E - O.D. roof curb (std.)

F - Recommended roof opening (MAX). (I.D.of factory built prefab curb).

G - Shipping Weights (lbs).

## **FEATURE**

- Ultra low profile
- AMCA Air & Sound Licensed
- UL 705 listed (optional)
- UPS shipping carton
- 5 year warranty
- 140° Max. airstream temperature

## **CONSTRUCTION**

- Aluminum construction
- Stainless steel exterior fasteners
- Backward curved centrifugal wheel
- Aluminum birdscreen
- Factory conduit wiring chase
- Electrical disconnect switch
- Precision balanced to ISO 1940

## MOTOR

- External rotor design
- Permanently lubricated bearings
- 3 year warranty
- Internal thermal protection
- 100% speed controllable
- 115/1/60 and 230/1/60/50 compatible
- Enclosed and continuous duty

FAN SPECIFICATIONS								MOTOR SPECIFICATIONS					
Line	Qty.	Model No.	Tag	CFM	SP	Fan RPM	BHP	Sones	HP	Volts	Phase	Hertz	Encl
I													
2													
3													
4													
5													

ACCESSORY ITEMS	I	2	3	4	5	ACCESSORY ITEMS	I	2	3	4	5

Project:	Submitted:
Customer:	Approved:
Location:	