

MODEL TXB-UL762					Upblast Belt Drive Centrifugal Restaurant Roof Exhauster								Ventilator with Open Drip-proof Motor and Drive Assembly	
Model TXB	Motor Hp	Max. BHP	RPM	Sones @ 1/4 SP	CFM at Static Pressure								115/1/60*	208-230/460/3/60
					0	1/4	3/8	1/2	5/8	3/4	1	1 1/4	Stock No.	Stock No.
8	1/4	0.10	1520	9.8	818	681	628	526	384	-	-	-	TXB08RHULML1S	N/A
	1/4	0.22	1995	15.9	1074	955	912	875	834	766	583	-	TXB08RHULMH1S	N/A
	1/3	0.33	2270	19.9	1222	1111	1070	1034	1001	969	858	697	TXB08RHULPH1S	N/A
10	1/4	0.24	1365	11.2	1339	1146	1033	903	750	558	-	-	TXB10RHULMH1S	N/A
	1/3	0.34	1530	13.9	1501	1334	1238	1133	1015	881	530	-	TXB10RHULPH1S	N/A
	1/2	0.52	1765	18.4	1731	1589	1511	1428	1338	1240	1015	727	TXB10RHULQH1S	TXB10RHULQH3S
12	1/4	0.27	1500	13.7	1507	1353	1281	1201	1107	996	703	-	TXB12RHULMH1S	N/A
	1/3	0.35	1645	17.0	1652	1509	1446	1378	1302	1215	-	-	TXB12RHULPH1S	N/A
	1/2	0.54	1890	23	1898	1769	1715	1659	1600	1537	1390	1211	TXB12RHULQH1S	TXB12RHULQH3S
15	1/4	0.26	995	11.1	2167	2015	1672	1458	1170	572	-	-	TXB15RHULMH1S	N/A
	1/3	0.35	1095	13.5	2385	2103	1947	1774	1570	1305	-	-	TXB15RHULPH1S	N/A
	1/2	0.53	1255	17.8	2733	2490	2361	2223	2074	1906	1462	-	TXB15RHULQH1S	TXB15RHULQH3S
	3/4	0.79	1435	22	3125	2914	2804	2690	2571	2444	2155	1782	TXB15RHULRH1S	TXB15RHULRH3S
	1	1.07	1590	26	3463	3273	3175	3075	2972	2864	2631	2362	TXB15RHULSH1S	TXB15RHULSH3S
16	1/2	0.51	1000	15.5	3270	2986	2820	2628	2414	2161	1105	-	TXB16RHULQH1S	TXB16RHULQH3S
	3/4	0.71	1110	19.0	3629	3367	3249	3073	2906	2716	2243	-	TXB16RHULRH1S	TXB16RHULRH3S
	1	0.98	1235	23	4038	3794	3693	3574	3410	3261	2902	-	TXB16RHULSH1S	TXB16RHULSH3S
18	1/2	0.50	940	12.5	3382	3058	2886	2696	2488	2243	-	-	TXB18RHULQH1S	TXB18RHULQH3S
	3/4	0.74	1075	16.0	3868	3584	3442	3288	3123	2950	2786	2816	TXB18RHULRH1S	TXB18RHULRH3S
	1	1.04	1200	19.4	4318	4063	3937	3808	3668	3521	3201	3621	TXB18RHULSH1S	TXB18RHULSH3S
	1 1/2	1.49	1350	24	4857	4630	4518	4406	4291	4169	3906	-	TXB18RHULTH1S	TXB18RHULTH3S
20	3/4	0.77	875	15.7	4688	4264	4034	3784	3482	3067	1902	2072	TXB20RHULRH1S	TXB20RHULRH3S
	1	1.07	975	19.1	5224	4848	4646	4436	4208	3944	3175	3808	TXB20RHULSH1S	TXB20RHULSH3S
	1 1/2	1.60	1115	24	5974	5649	5477	5300	5116	4923	4470	-	TXB20RHULTH1S	TXB20RHULTH3S
24	1/3	0.33	495	8.0	4555	3731	3018	-	-	-	-	-	TXB24RHULPH1S	TXB24RHULPH3S
	1/2	0.50	565	10.3	5199	4519	4063	3346	-	-	-	-	TXB24RHULQH1S	TXB24RHULQH3S
	3/4	0.75	650	13.6	5981	5413	5072	4661	4099	2979	-	-	TXB24RHULRH1S	TXB24RHULRH3S
	1	1.03	720	16.6	6626	6123	5835	5509	5124	4623	-	2245	TXB24RHULSH1S	TXB24RHULSH3S
	1 1/2	1.51	820	22	7546	7113	6874	6616	6332	6010	5146	5433	TXB24RHULTH1S	TXB24RHULTH3S
	2	2.00	900	26	8282	7892	7681	7457	7216	6956	6339	-	N/A	TXB24RHULVH3S

Power ratings (BHP) do not include transmission losses.

Performance certified is for installation type A-free inlet, free outlet. Performance ratings include the effects of birdscreen in the airstream.

The sound ratings shown are loudness values in fan sones @ 5' (1.5m) in a hemispherical free field calculated per AMCA Standard 301.

Values shown are for installation Type A-Free inlet fan sone levels.

***Tri-voltage (115-208-230) is standard on 3/4 through 1 1/2 Hp Single phase motors. Tri-voltage is available for the 1/2 Hp motors. Inquire for price and delivery.**