

MODEL TXD					Upblast Direct Drive Centrifugal Roof/Sidewall Exhauster										Ventilator with Open Drip-proof Motor	
Model TXD	Motor Hp	Max. BHp	RPM	Sones @ 1/8 SP	CFM at Static Pressure										115/1/60	208-230/1/60
					0	1/8	1/4	3/8	1/2	5/8	3/4	7/8	1	Stock No.	Stock No.	
6	1/10	0.09	1795	7.7	410	370	328	276	203	-	-	-	-	TXD06JH1AS	TXD06JH1CS	
8	1/4	0.07	1130	6.2	886	783	644	441	-	-	-	-	-	TXD08MM1AS	TXD08MM1CS	
	1/4	0.24	1740	13.8	1364	1300	1232	1158	1072	960	851	698	510	TXD08MH1AS	TXD08MH1CS	
10	1/4	0.27	1650	14.7	1527	1460	1398	1325	1236	1129	1011	883	747	TXD10RHULMH1AS	TXD10RHULMH1CS	
12	1/4	0.16	1140	9.6	1616	1487	1338	1161	983	760	462	-	-	TXD12RHULMM1AS	TXD12RHULMM1CS	
	1/2	0.55	1730	21.0	2453	2364	2281	2196	2097	1985	1867	1751	1638	TXD12RHULQH1AS	TXD12RHULQH1CS	
14	1/4	0.25	1130	10.4	2060	1939	1798	1638	1439	1177	856	-	-	TXD14RHULMM1AS	TXD14RHULMM1CS	
15	1/2	0.41	1155	13.2	2786	2653	2491	2313	2104	1863	1623	1362	969	TXD15RHULQM1AS	TXD15RHULQM1CS	

Speed (RPM) shown is nominal. Performance is based on actual speed of test.

Performance certified is for installation type A-free inlet, free outlet.

Performance ratings include the effects of birdscreens in the airstream.

The sound ratings shown are the loudness values in the fan sones @ 5' (1.5m) in an hemispherical free field calculated per AMCA Standard 301.

Values shown are for Installation Type A-Free inlet fan sone levels.

Performance Data at Reduced Speed													
Model TXD	Motor Hp	Max. BHp	RPM	Sones @ 1/8 SP	CFM at Static Pressure								
					0	1/8	1/4	3/8	1/2	5/8	3/4	7/8	1
6-1550	1/10	0.02	1150	2.4	253	185	-	-	-	-	-	-	-
		0.05	1470	5.1	335	286	227	115	-	-	-	-	-
8-1075	1/4	0.01	680	1.2	533	302	-	-	-	-	-	-	-
		0.03	860	3.2	674	525	-	-	-	-	-	-	-
		0.05	1040	5.2	815	701	536	-	-	-	-	-	-
8-1625	1/4	0.10	1405	9.3	1101	1021	930	814	673	468	-	-	-
10-1625	1/4	0.10	1185	7.8	1097	1007	896	742	561	318	-	-	-
		0.20	1500	12.3	1388	1316	1245	1155	1043	914	771	615	407
12-1075	1/4	0.03	680	3.3	964	712	352	-	-	-	-	-	-
		0.08	905	6.5	1283	1116	897	649	-	-	-	-	-
12-1625	1/2	0.17	1175	10.2	1666	1540	1399	1228	1060	855	599	-	-
		0.32	1445	14.9	2049	1945	1844	1724	1586	1446	1310	1152	969
14-1075	1/4	0.05	680	3.6	1240	1011	609	-	-	-	-	-	-
		0.13	905	6.8	1650	1491	1294	1020	617	-	-	-	-
15-1140	1/2	0.05	570	3.1	1375	1027	422	-	-	-	-	-	-
		0.18	885	8.2	2135	1948	1710	1406	1087	-	-	-	-

Model in reduced speed table indicates size and motor RPM of base unit.

Performance is for that base unit operated at a reduced speed using the solid state speed control accessory.

AMCA Seal for sound rating does not apply to units with speed control.

Use 5 AMP Speed Control for motors 1/3 HP and smaller.

Use 10 AMP Speed Control for motors 1/2.