
## **UBS- BELT DRIVE UPBLAST PROPELLER ROOF EXHAUSTER**



48

54

37

26

56 52

## **STANDARD CONSTRUCTION FEATURES**

- Galvanized steel butterfly dampers.
- Galvanized steel windband.
- Lifting eyes at all four corners of curb cap.
- · Galvanized curb cap with fully welded corners.
- Heavy galvanized schedule 40 pipe frame.
- · Cast iron pillow block bearings with lube fittings. average life of 200.000 hours.
- V-belt drive with adjustable motor sheave. (Standard through 3 HP)
- Nationally recognized and locally serviced motor.
- Heavy epoxy coated steel hub plate. Keyed to fan shaft.
- Die formed epoxy coated steel propeller blades.
- Integral galvanized steel rain channel.

16

450

• Stainless steel damper rod.



							MET	AVG.	
MODEL UBS	Α	В	с	D	E	F	WIND SHROUD	FAN PANEL	SHIP WT. LBS.
24	30	26	20	32	28	31	18	16	250
30	36	29	21	38	34	37	18	16	325
36	42	31	21	44	40	43	18	16	350
42	48	34	22	50	46	49	18	16	425

55

18

- Outside Diameter of Windband.
- Height of Unit Above Curb Cap.
- Maximum Depth of Unit Below Top of Curb, Actual Depth Varies with Motor Size.
- Inside Dimension of Square Curb Cap.
- Minimum Inside Dimension of Curb Opening Required for Adequate Clearance of Fan Frame.
- Outside Dimension of Factory Built Prefab Curb.

FAN SPECIFICATIONS										MOTOR SPECIFICATIONS								
Line	Qty.	Model No.	Tag	CFM	1 SP		Fan RPM		BHP	Sones	HP	Volts	Phase		Hertz	: E	Encl	
Ι																		
2																		
3																		
4																		
5																		
ACCESSORY ITEMS			I	2	3	4	5	AC	CESS	ORY ITE	MS	I	2	3	4	5		
							1							-				
Proie	Project: Submitted:																	

Project:	Submitted:
Customer:	Approved:
Location:	, .pp. 0.001